


Manual

Air compressor

116 PSI

Pressure



Applies for:

Code	Model
19360	COMP-50LV

COMP-50LV

CAUTION



Read this manual thoroughly
before using the tool.

1
YEAR WARRANTY
1
YEAR WARRANTY

Technical Data.....	3
Power Requirements.....	3
 General Power Tool Safety Warnings.....	4
 Safety Warnings for Air Compressors.....	5
Parts.....	6
Preparation.....	7
Startup.....	8
Maintenance.....	8
Accessories and replacement parts.....	9
Troubleshooting.....	10
Authorized Service centers.....	11
Warranty Policy.....	12

CAUTION

To gain the best performance of the tool, prolong the duty life, make the Warranty valid if necessary, and to avoid hazards of fatal injuries please read and understand this Manual before using the tool.

Keep this manual for future references.

The illustrations in this manual are for reference only. They might be different from the real tool.

Use and care recommendations

 **ONLY CONNECT** equipment if its airflow (**CFM and PSI**) is within the range that the compressor can provide.

 **DO NOT OPERATE THE COMPRESSOR WITHOUT OIL.**
The warranty will be voided if a lubricating oil other than SAE-30 is used.

 **IF THE COMPRESSOR DOESN'T WORK AFTER A LONG PERIOD OF INACTIVITY**, deactivate the thermal switch as instructed on the label attached to the tank. If the compressor doesn't work or turn on, visit to a TRUPER Authorized Service Center.

 **INSTALL** the wheels and the rubber supports to keep the compressor level (page 7).

 Perform periodic **MAINTENANCE** to your machine (page 8).

COMP-50LV

Code •	19360
Description •	Air Compressor
Voltage •	127 V~
Frequency •	60 Hz
Motor Power •	Rated: 2 1/2 Hp Maximum: 3 1/2 Hp
Current •	12 A
Maximum Pressure •	116 PSI
Speed •	3 450 RPM
Continuous Air flow •	4.4 CFM - 40 PSI 3.4 CFM - 90 PSI
Tank Capacity •	13.2 Gal
Conductors •	14 AWG x 3C with 221 °F insulation temperature
Insulation •	Class I
Power Cord Grips used in this product: Type Y. Tool Build Quality: Basic insulation Thermal insulation on motor winding: Class B	

⚠ WARNING Avoid the risk of electric shock or severe injury. When the power cable gets damaged it should only be replaced by the manufacturer or at a TRUPER® Authorized Service Center. The build quality of the electric insulation is altered if spills or liquid gets into the tool while in use. Do not expose to rain, liquids and/or dampness.


⚠ WARNING Before gaining access to the terminals all power sources should be disconnected.



Power Requirements

⚠ WARNING • The tool must be grounded while not in use to prevent electric shock.

- Plug the tool plug into a properly grounded outlet or socket as shown in example A. Not all outlets or sockets are properly grounded, if in doubt, check with a qualified electrician.
- If the outlet you plan to use for your tool is a 2-pole outlet (2 holes), DO NOT REMOVE OR ALTER THE GROUND CONDUCTOR FROM YOUR PLUG UNDER ANY CIRCUMSTANCES. Use a temporary adapter as shown in example B and always connect the ground conductor lug as indicated.



⚠ CAUTION

⚠ CAUTION A power extension cord is not recommended to use with a compressor. Using an extension causes voltage drop, power loss in the motor and overheating. Instead of using an extension cord, increase the compressor's action scope connecting a longer length of hose into the outlet. Connect additional hose lengths as required. Likewise, if needing to use a pneumatic tool outdoors in humid environment or even when raining, operate the compressor from the inside keeping it guarded from humidity. Operate the pneumatic tool connected to the compressor through additional lengths of hose without the risk of electric shock.

- In the event of connecting the compressor into a circuit protected with fuses, use delay action fuses type "D".



WARNING

This tool **SHALL BE USED** with 115 V ~ 127 V-feed. Using a **DIFFERENT VOLTAGE WILL SEVERELY DAMAGE** the product.



⚠ WARNING! Read carefully all safety warnings and instruction listed below. Failure to comply with any of these warnings may result in electric shock, fire and / or severe damage. **Save all warnings and instructions for future references.**

Work area

Keep your work area clean, and well lit.

Cluttered and dark areas may cause accidents.



Never use the tool in explosive atmospheres, such as in the presence of flammable liquids, gases or dust.

Sparks generated by power tools may ignite the flammable material.



Keep children and bystanders at a safe distance while operating the tool.

Distractions may cause loss of control.

**Electrical Safety**

The tool plug must match the power outlet. Never modify the plug in any way. Do not use any adapter plugs with grounded power tools.

Modified plugs and different power outlets increase the risk of electric shock.



Avoid body contact with grounded surfaces, such as pipes, radiators, electric ranges and refrigerators.

The risk of electric shock increases if your body is grounded.

Do not expose the tool to rain or wet conditions.

Water entering into the tool increases the risk of electric shock.

Do not force the cord. Never use the cord to carry, lift or unplug the tool. Keep the cord away from heat, oil, sharp edges or moving parts.

Damaged or entangled cords increase the risk of electric shock.

When operating a tool outdoors, use an extension cord suitable for outdoor use.

Using an adequate outdoor extension cord reduces the risk of electric shock.

If operating the tool in a damp location cannot be avoided, use a ground fault circuit interrupter (GFCI) protected supply.

Using a GFCI reduces the risk of electric shock.

Personal safety

Stay alert, watch what you are doing and use common sense when operating a tool. Do not use a power tool while you are tired or under the influence of drugs, alcohol or medication.

A moment of distraction while operating the tool may result in personal injury.

Use personal protective equipment. Always wear eye protection.

Protective equipment such as safety glasses, anti-dust mask, non-skid shoes, hard hats and hearing protection used in the right conditions significantly reduce personal injury.



Prevent unintentional starting up. Ensure the switch is in the "OFF" position before connecting into the power source and / or battery as well as when carrying the tool.

Transporting power tools with the finger on the switch or connecting power tools with the switch in the "ON" position may cause accidents.

**Service**

Repair the tool in a TRUPER Authorized Service Center using only identical spare parts.

This will ensure that the safety of the power tool is maintained.



Children or people with reduced physical, sensory or mental capabilities shall not operate the tool, neither inexperienced people or without knowledge in the use of the tool, unless supervised by a person responsible of their safety or if receiving previous instructions about the tool operation.

Children shall be kept under supervision to double-check they will not play with the tool. Tight supervision shall be used with children or disabled persons to prevent from using or being close to any household tool.



Safety warnings for pneumatic compressors

TRUPER®

Before using the compressor

CAUTION • The pressurestat produces sparks when working. If sparks make contact with gasoline vapors or other solvents they can ignite causing fire or explosion. Always operate the compressor in a properly ventilated area. Do not operate in closed spaces. Do not smoke while spraying. Do not spray in flammable environments. Keep the compressor as far away as possible from the spraying area.

CAUTION • Solvents like trichlorethane and methylene chloride can suffer a chemical reaction with the aluminum used in the spraying guns, paint pumps, etc., and can cause an explosion. If using these solvents use only stainless steel spraying materials. This will not affect the air compressor but can have an effect on the equipment being used.

DANGER • For no reason at all carry out soldering jobs in the air compressor tank. It creates an extremely dangerous condition. Carrying soldering jobs in the tank will void the warranty.

DANGER • Never use the compressor outdoors when raining or onto wet surfaces. An electric shock can strike.

CAUTION • Check the maximum pressure specified by the manufacturer for pneumatic tools and accessories. The compressor's output pressure shall be regulated so that will never exceed the maximum specified pressure. • Save the labels and nameplates. On them there is important safety information. If the information on those labels cannot be read or is missing contact a TRUPER Authorized Service Center to get spares.

CAUTION • For no reason at all modify the pressurestat or the pressure release valve. Doing it makes the warranty void. Were adjusted in the factory to the maximum pressure for this unit.

CAUTION • Be sure you read all the labels in the paints or toxic materials you spray. Follow the safety instructions. Wear a breathing mask if there is any possibility to inhale the material being sprayed. Read the breathing mask instructions to double check it will provide the necessary protection.

CAUTION • Always wear safety glasses when using the air compressor. • To allow an adequate cooling ventilation, the compressor shall be kept at a minimum 12" away from the nearest wall in a well-ventilated area. • Environment temperature recommended to operate the compressor is from 32 °F to 95 °F

When using the compressor

CAUTION • Do not aim nozzles, sprayers or the air jet towards people or animals.

WARNING • Never inhale directly the compressed air produced by the air compressor. Is not suitable as breathing air.

WARNING • Do not adjust the regulator above the maximum pressure labeled in the accessory. Otherwise the compressor might burst.

• Operate the compressor in a leveled surface. • Keep the compressor well ventilated. Do not cover it while in use.

CAUTION • The compressor gets hot while operating. Do not touch it or allow children get close while or immediately after is been used. Do not use it without the motor cover in place. Work as far away as possible from flammable objects or liquids.

• The air hose components may get hot while being used. Allow the components to cool down before disconnecting. • Do not use the air hose to carry or move the compressor. • Do not leave the compressor connected into the power supply when unattended for long periods of time. Disconnect the tool after using it.

• Using accessories not recommended by TRUPER can result in personal injuries.

• High temperatures are produced under the compressor cover and there are also parts in movement. To prevent burns or other kind of injuries do not operate with the cover removed from its place. Allow the compressor parts to cool down before handling or servicing.

• Do not release any connections when the tank is under pressure.

After using the compressor

• Keep in mind the compressor starts automatically. Always turn off the compressor. Remove the plug from the power outlet, purge and release all the pressure from the system before servicing the compressor and when it is not in use.


• Drain humidity from the tank often. A dry and clean tank will help against corrosion.

• Pull the pressure release valve ring daily to ensure the valve works properly and to remove any obstruction.

• If transporting the compressor fasten it correctly. Release the tank pressure before carrying.

• Protect the air hose and power cable from damage or punctures. Inspect weekly to detect any weak or worn out points. Replace if necessary.






- The air compressor delivers energy to pneumatic tools as versatile as power tools, therefore, it can be used to drill, screw, nail, rivet, staple, chisel, polish, torch, clean, paint, etc.
- The compressor is totally automatic, controlled with a pressurestat that stops the motor when the tank pressure reaches the maximum level and start back when the level is lower to 87 PSI
- The compressor shall be connected into power supply protected with an adequate thermos-differential switch (thermal-magnetic).

Assembly

- Carefully lay down the compressor onto a flat, leveled and solid surface to assemble the wheels (A) and the front supports (B) with their screws and hex nuts as shown in the illustration.
- Set the compressor up and screw on the air filter (C) on one side of the carter as indicated in the illustration.




Oil

CAUTION • Replace the transport cap (D) with the work cap (D¹) included.

- Check the oil verifying spyhole (E). If oil level is not in the middle point (red circle), remove the tank cap (D¹) and fill up the deposit with compressor lubricating oil SAE-30 up to the indicated level.

CAUTION • Check the oil level when starting the job.

- Leave the compressor running a few minutes with the air valve fully open to allow the correct distribution of the lubricant.



ON and OFF



- Before operating the compressor set it onto a flat leveled surface with good ventilation and away from flammable objects, like drapes, etc. Leave at least 12" free space around the compressor to allow air circulation.
- Connect the plug to the power supply. To prevent tripping or damaging the cable, double check the cable is not an obstacle.
- Lift the switch (A) to turn ON the compressor. The motor will start and will fill the tank to maximum pressure. Then, it will automatically turn OFF. While the compressor is being used and to keep the constant pressure indicated in the gauge (B) it will start again when the pressurestat is detecting low pressure.
- To turn OFF the compressor just press the switch. Then, release the air remaining in the tank by pulling the pressure release valve ring (C).

CAUTION • Never unplug the compressor from the power supply in order to turn it OFF. If the power supply is accidentally cut, do not forget to turn the compressor OFF correctly.

• The compressor is built with a thermal switch (D) that prevents the motor from overheating. The motor turns OFF when the switch is activated. To restart the motor, follow these steps:

1. Press the switch (A) to double check the compressor is OFF.
2. Leave the compressor cooling down at least 5 minutes.
3. Press the thermal switch (D) placed aside the carter.
4. Lift the switch (A) to turn ON the compressor.

NOTE: If the unit turns OFF again, please go to a TRUPER Authorized Service Center.



Operation

- Connect one end of the air hose to the compressor outlet (E).
- Connect the other end of the air hose to the inlet in the pneumatic tool (not included). Double check the connections match.
- Adjust the air pressure outlet with the pressure gauge (F). Turn the knob to the right to increase the outlet pressure. Turn it to the left to decrease pressure until getting the desired pressure indicated in the outlet gauge (G).

CAUTION • Adjusting pressure must be carried out having the regulated outlet valve open.

- After connecting the compressor to the air line, run it loaded to its maximum pressure and double check it works correctly.
- Check there are no leaks in the air line. Turn OFF the compressor to repair any leak detected.


CAUTION • The motor and the cover may reach high temperatures. When working with the compressor avoid touching that zone to prevent burns.

Maintenance

Daily preventive maintenance

OIL: Check the oil level in the crankcase (A) and top up if necessary. If your compressor is unused daily, check the crankcase oil level before starting. Change the oil after 150 hours of use.


Oil tank capacity 8.5 oz (250 ml)



■ Oil functioning level ■ Oil refill level




Oil Change

• After the 50 hours operation change oil. Remove the drain cap (B). Set back the cap and fill up the tank as indicated in page 7. The subsequent oil change shall be carried out each 150 hours' work.



Cleansing and Care


- To ensure the adequate cooling of the motor always keep the air vents clean and free of obstructions.
- Regularly inspect all the mounting screws and make sure are correctly tight. If any of the screws is loose, tighten immediately.
- Once a week open and clean the inside of the air filter (**b**) using compressed air. After 50 hours functioning replace the air filter (**C**).



- After operating the compressor for 16 hours, open the drain valve (**D**) to eliminate the water stored in the tank due to condensation.
- After each use disconnect the compressor and release the air pressure in the tank pulling the pressure release valve ring (**E**).

Service

- Any other service or repair in the compressor shall only be carried out in a TRUPER Authorized Service Center. Service and maintenance carried out by unqualified people may be dangerous and can cause personal injuries and makes the Warranty void.



Accesories and replacement parts

List of available accesories and replacement parts

Component	Code	Item	Description
	19325	R27-COMP-25/50L	Air intake filter
	102067	R63-COMP-10L	Pressure gauge
	102068	R52-COMP-50LT	Pressure gauge
	19328	R30-COMP-25/50L	Guard
	102082	R63-COMP-50LT	Rubber feet set
	103320	R-COMP-50LV	2-Pc 7" x 1 1/2" wheel set

Problem	Cause	Solution
The motor is not working.	<ul style="list-style-type: none"> • No power. • Fuse is blown . • Thermal switch is activated. • Pressurestat is faulty . 	<ul style="list-style-type: none"> • Be sure the cable is connected. Check the fuse-circuit switch. • Replace the blown fuse. • Press the thermal switch button to restart. • Go to a TRUPER Authorized Service Center.
The motor is buzzing but is not running or runs slowly.	<ul style="list-style-type: none"> • Tension Drop. • Motor winding in short or open. • Check valve or faulty pressurestat. • Compressed air in the cylinder. 	<ul style="list-style-type: none"> • Check with a voltmeter. Minimum tension shall be 115 V ~ • Go to a TRUPER Authorized Service Center. • Go to a TRUPER Authorized Service Center. • Press the switch 15 seconds into the position "O" . Then, lift to the position "I" .
Fuses blow up. The circuit switch is triggered repeatedly.	<ul style="list-style-type: none"> • Wrong fuse capacity, overloaded circuit. • Fault in the check valve or pressurestat. 	<ul style="list-style-type: none"> • Check the right fuse is being used. Use a time delay fuse. Disconnect other devices using the same circuit or operate the compressor using an independent circuit. • Go to a TRUPER Authorized Service Center.
Thermal overload protection causes interruptions repeatedly.	<ul style="list-style-type: none"> • Tension drop. • Clogged air filter. • Lack of adequate ventilation. • Environment temperature is too high. 	<ul style="list-style-type: none"> • Check with a voltmeter. Minimum tension shall be 115 V • Clean the air filter. • Move the compressor to an area with adequate ventilation. • Move the compressor to an area with adequate temperature.
Pressure in the tank drops when the motor stops.	<ul style="list-style-type: none"> • Loose connections (couplings, pipes, etc.). • Purge tap is open. • Check valve leaks. 	<ul style="list-style-type: none"> • Check to detect air leaks. Use sealant tape in all the leaky connections. • Tighten the purge key. • Disassemble the check valve. Clean or replace. <p>DANGER DO NOT DISASSEMBLE THE CHECK VALVE WITH AIR IN THE TANK. PURGE THE TANK FIRST TO RELEASE ALL THE PRESSURE.</p>
Excessive humidity in the discharge air.	<ul style="list-style-type: none"> • Excessive water in the tank. • High humidity. • Clogged entry filter . 	<ul style="list-style-type: none"> • Drain the tank opening the drain valve. • Move the compressor to an area with less humidity. Use a filter in the air pipes. • Clean or replace filter.
The motor runs continuously without stopping.	<ul style="list-style-type: none"> • Faulty pressurestat. • Excessive air use. 	<ul style="list-style-type: none"> • Go to a TRUPER Authorized Service Center to replace the pressurestat. • The compressor is not big enough to satisfy the CFM of the pneumatic tool requirements being used.
The compressor vibrates.	<ul style="list-style-type: none"> • Loose mounting bolts. • The tank rubber bases are not installed or are worn. 	<ul style="list-style-type: none"> • Tighten all the bolts and screws. • Install or replace the rubber bases.
Air output lower to normal.	<ul style="list-style-type: none"> • The purge tap is open. • Admission filter is dirty. • Leak in a connection. 	<ul style="list-style-type: none"> • Tighten the purge tap. • Clean or replace the admission filter. • Tighten the connections. Check to detect air leaks. Use sealant tape in all the leaky connections. Replace the damaged or broken hoses.

Authorized Service Centers

TRUPER®

In the event of any problem contacting a TRUPER Authorized Service Center, please see our webpage WWW.TRUPER.COM to get an updated list, or call our toll-free numbers **800 690-6990** or **800 018-7873** to get information about the nearest Service Center.

AGUASCALIENTES	DE TODO PARA LA CONSTRUCCIÓN GRAL. BARRAGÁN #1201, COL. GREMIAL, C.P. 20030, AGUASCALIENTES, AGS. TEL.: 449 994 0537		MORELOS	FIX FERRETERÍAS CAPITÁN ANZURES #95, ESQ. JOSÉ PERDIZ, COL. CENTRO, C.P. 62740, CUAUTLA, MOR. TEL.: 735 352 8931
BAJA CALIFORNIA	SUCRASAL TIJUANA AV. LA ENCANTADA, LOTE #5, PARQUE INDUSTRIAL EL FLORIDO II, C.P. 22244, TIJUANA, B.C. TEL.: 664 969 5100		NAYARIT	HERRAMIENTAS DE TEPIC MAZATLÁN #117, COL. CENTRO, C.P. 63000, TEPIC, NAY. TEL.: 311 258 0540
BAJA CALIFORNIA SUR	FIX FERRETERÍAS FELIPE ANGELES ESQ. RUIZ CORTÍNEZ S/N, COL. PUEBLO NUEVO, C.P. 23670, CD. CONSTITUCIÓN, B.C.S. TEL.: 613 132 1115		NUEVO LEÓN	SUCRASAL MONTERREY CARRETERA LAREDO #300, 1B MONTERREY PARKS, COLONIA PUERTA DE ANÁHUAZ, C.P. 66052, ESCOBEDO, NUEVO LEÓN, TEL.: 81 8352 8791 / 81 8352 8790
CAMPECHE	TORNILLERÍA Y FERRETERÍA AAA AV. ALVARO OBREGÓN #324, COL. ESPERANZA C.P. 24080 CAMPECHE, CAM. TEL.: 981 815 2808		OAXACA	FIX FERRETERÍAS AV. 20 DE NOVIEMBRE #910, COL. CENTRO, C.P. 68300, TUXTEPEC, OAX. TEL.: 287 106 3092
CHIAPAS	FIX FERRETERÍAS AV. CENTRAL SUR #27, COL. CENTRO, C.P. 30700, TAPACHULA, CHIS. TEL.: 962 118 4083		PUEBLA	SUCRASAL PUEBLA AV. PERIFÉRICO #2-A, SAN LORENZO ALMECATLA, C.P. 72710, CUATLACINGO, PUE. TEL.: 222 282 8282 / 84 / 85 / 86
CHIHUAHUA	SUCRASAL CHIHUAHUA AV. SILVESTRE TERRAZAS #128-11, PARQUE INDUSTRIAL BAFAR, CARRETERA MÉXICO CUAUHTÉMOC, C.P. 31415, CHIHUAHUA, CHIH. TEL. 614 434 0052		QUERÉTARO	ARU HERRAMIENTAS S.A DE C.V. AV. PUERTO DE VERACRUZ #110, COL. RANCHO DE ENMEDIO, C.P. 76842, SAN JUAN DEL RÍO, QRO. TEL.: 427 268 4544
CIUDAD DE MÉXICO	FIX FERRETERÍAS EL MONSTRUO DE CORREGIDORA, CORREGIDORA # 35, COL. CENTRO, C.P. 06060, CUAUHTEMOC, CDMX. TEL.: 55 5522 5031 / 5522 4861		QUINTANA ROO	FIX FERRETERÍAS CARRETERA FEDERAL MZ. 46 LT. 3 LOCAL 2, COL. EJIDAL, C.P. 77710 PLAYA DEL CARMEN, Q.R. TEL.: 984 267 3140
COAHUILA	SUCRASAL TORREÓN CALLE METAL MECÁNICA #280, PARQUE INDUSTRIAL ORIENTE, C.P. 27287, TORREÓN, COAH. TEL.: 871 209 68 23		SAN LUIS POTOSÍ	FIX FERRETERÍAS AV. UNIVERSIDAD #1850, COL. EL PASEO, C.P. 78320, SAN LUIS POTOSÍ, SLP. TEL.: 444 822 4541
COLIMA	BOMBAS Y MOTORES BYMTESA DE MANZANILLO BLVD. MIGUEL DE LA MADRID #190, COL. 16 DE SEPTIEMBRE, C.P. 28239, MANZANILLO, COL. TEL.: 314 332 1986 / 332 8013		SINALOA	SUCRASAL CULIACÁN AV. JESÚS KUMATE SUR #4301, COL. HACIENDA DE LA MORA, C.P. 80143, CULIACÁN, SIN. TEL.: 667 173 9139 / 173 8400
DURANGO	TORNILLOS ÁGUILA, S.A. DE C.V. MAZURIO #200, COL. LUIS ECHEVERRÍA, DURANGO, DGO. TEL.: 618 817 1946 / 618 818 2844		SONORA	FIX FERRETERÍAS CALLE 5 DE FEBRERO #517, SUR LT. 25 MZ. 10, COL. CENTRO, C.P. 85000, CD. OBREGÓN, SON. TEL.: 644 413 2392
ESTADO DE MÉXICO	SUCRASAL CENTRO JILOTEPEC PARQUE INDUSTRIAL # 1, COL. PARQUE INDUSTRIAL JILOTEPEC, JILOTEPEC, EDO. DE MÉX. C.P. 54257 TEL.: 761 782 9101 EXT. 5728 Y 5102		TABASCO	SUCRASAL VILLAHERMOSA CALLE 60 LOTES 1, 2 Y 3 MZ. #1, COL. INDUSTRIAL, 2A ETAPA, C.P. 86010, VILLAHERMOSA, TAB. TEL.: 993 353 7244
GUANAJUATO	CÍA. FERRETERA NUEVO MUNDO S.A. DE C.V. AV. MÉXICO - JAPÓN #225, CD. INDUSTRIAL, C.P. 38010, CELAYA, GTO. TEL.: 461 617 7578 / 79 / 80 / 88		TAMAULIPAS	VM ORINGS Y REFACCIONES CALLE ROSITA #527 ENTRE 20 DE NOVIEMBRE Y GRAL. RODRÍGUEZ, FRACC. REYNOSA, C.P. 88700, REYNOSA, TAMS. TEL.: 899 926 7552
GUERRERO	CENTRO DE SERVICIO ECLIPSE CALLE PRINCIPAL MZ.1 LT. 1, COL. SANTA FE, C.P. 39010, CHILPANCINGO, GRO. TEL.: 747 478 5793		TLAXCALA	SERVICIOS Y HERRAMIENTAS INDUSTRIALES PABLO SIDAR #132, COL. .BARRIO DE SAN BARTOLOMÉ, C.P. 90970, SAN PABLO DEL MONTE, TLAX. TEL.: 222 271 7502
HIDALGO	FERREPRECIOS S.A. DE C.V. LIBERTAD ORIENTE #304 LOCAL 30, INTERIOR DE PASAJE ROBLEDO, COL. CENTRO, C.P. 43600, TULANCINGO, HGO. TEL.: 775 753 6615 / 775 755 6616		VERACRUZ	LA CASA DISTRIBUIDORA TRUPER BLVD. PRIMAVERA, ESQ. HORTENSIA S/N, COL. PRIMAVERA C.P. 93308, POZA RICA, VÉR. TEL.: 782 823 8100 / 826 8484
JALISCO	SUCRASAL GUADALAJARA AV. ADOLFO A. HORN # 6800, COL. SANTA CRUZ DEL VALLE, C.P.: 45655, TLAJOMULCO DE ZUÑIGA, JAL. TEL.: 33 3606 5285 AL 90		YUCATÁN	SUCRASAL MÉRIDA CALLE 33 #600 Y 602, LOCALIDAD ITZINCAB Y MULSAY, MPIO. UMÁN, C.P. 97390, MÉRIDA, YUC. TEL.: 999 912 2451
MICHOACÁN	FIX FERRETERÍAS AV. PASEO DE LA REPÚBLICA #3140-A, COL. EX-HACIENDA DE LA HUERTA, C.P. 58050, MORELIA, MICH. TEL.: 443 334 6858			

Code	Model	Brand
19360	COMP-50LV	TRUPER®

Warranty. Duration: 1 year. Coverage: parts, components and workmanship against manufacturing or operating defects, except if used under conditions other than normal, when it was not operated accordance with the instructive, was altered or repaired by personnel not authorized by TRUPER®. To make the warranty valid, present the product, stamped policy or invoice or receipt or voucher, in the establishment where you bought it or in Corregidora 35, Centro, Cuauhtémoc, CDMX, 06060, where you can also purchase parts, components, consumables and accessories. It includes the costs of transportation of the product that derive from its fulfillment of its service network. Phone number 800-018-7873. Made in China. Imported by TRUPER, S.A. de C.V. Parque Industrial 1, Parque Industrial Jilotepec, Jilotepec, Edo. de Méx. C.P. 54257, Phone number 761 782 9100.

Stamp of the business. Delivery date:

