


TRUPER



LÓMUc E1 2 28 LaGf OEM - 1 2

an uera 1/2" super re or ada capas m cone iones meta

- b gt nfl yg j ut yl nfl yéu kl 2 qku yk p ryl zp 2l t 2l g rg g 2g vyl zpót
- Lut l Óut l z s l 2árñ gz yui flz 2gz kl s áÓs g kflygi p k gk j ut yl zuy 2l xfll v yu 2l nl rg s gt nfl yg á l ßg kl nays gj p ut l z
- el j t urun g gt 2 p 2uy l kflygz ñngygt 2ég flt ñ flq j ut 2 p flu
- ñ zu kus ñ z 2 p u



Certi a iones garant as

rodag aPagmtr

I Mpn	52 s
el asq	314"
Cr oar nqPa bM pP	40 s s
L qar é mPa s qM Mj	3A ñ nmj s ñ
Lar n ñ nq l asq	372 n
Cl o mpt a mPa e Pt M	G 2gku
É mraq	ñ
LMias	7 ñ


I Pá c d ñ p g e d m

Fabricado en M íco bajo las estrictas especificaciones de GRUPO TRUPER

El rendimiento en el uso de Truper



Manguera con refuerzo de tejido radial resistente a la alta presión



4 Capas



Empaque antifuga

Diseño cónico

Conector hembra

Diseño cónico, más ergonómico



Resorte que protege la manguera

Evita deformaciones